

CABLE DATA SHEET

| | |
|--------------------------|--|
| Part: | 32/0.2 Type 3 Def Stan |
| Description | Single core PVC insulated equipment wire |
| Conductor | 32/0.2mm Tinned Annealed Copper (Class 5 to IEC 60228) |
| Insulation | PVC (Type TI1 to BS EN 50636-3) |
| Insulation R/T | 0.60mm nominal, 0.50mm min. |
| Diameter over Insulation | 2.40mm min, 2.65mm max. |
| Conductor Resistance | 19.1 Ω /km at 20°C |
| Voltage Rating | 1500V AC max. |
| Current Rating | 6.0 amps (for guidance only as this will depend on the conditions of the installation) |
| Cable Weight | 16.9kg/km (nominal) |
| Temperature Range | -20°C to +85°C |
| Applicable Standards | Defence Standard 61-12 (Part 6) BS4808 |

Note 1: The upper temperature limits refer to maximum continuous temperature of the conductor due to the combination of ambient temperature and temperature rise due to current flow. The lower value may be subjected to slight flexing during normal operating life.

Note 2: The current carrying capacities are for wires carrying a continuous current in free air at an ambient temperature. Current carrying capacities will depend on circumstances but for general guidance the quoted current values will give a temperature rise of about 15°C in ambient temperatures up to 70°C for single, freely ventilated, insulated wires. Different values will apply when equipment wires are bunched.

T 0161 629 9333

F 0161 629 9444

W www.clyndercables.co.uk